

11kV XLPE LSZH Cable

Eland Product Group **A9M**

Application

Power cables for power networks, underground, outdoors and in cable ducting. In particular for installation where fire, smoke emission and toxic fumes create a potential threat. For installation where fire, smoke emission and toxic fumes create a potential threat to life and equipment.

Standards

BS7835, IEC 60754-1

Technical Data

Conductor

Class 2 stranded plain copper conductor to BS EN 60228:2005 (previously BS6360)

Conductor Screen

Semi-conducting material

Insulation

XLPE (Cross-Linked Polyethylene) Type GP8 to BS7655

Insulation Screen

Semi-conducting material

Metallic Screen

Individual and overall copper tape screen to BS6622

Filler

PETP (Polyethylene Terephthalate) fibres

Separator

Binding tape

Bedding

LSZH (Low Smoke Zero Halogen)

Armouring

Single Core: AWA (Aluminium Wire Armoured)
Multi-Core: SWA (Steel Wire Armoured)

Sheath

LSZH (Low Smoke Zero Halogen)

Sheath Colour

Red or Black

Voltage Rating

6350/11000V

Temperature Rating

0 to +90°C

Combustion Characteristics

Oxygen index: 35

Temperature index

280°C

HCL emission

0.5% in accordance with BS EN 50267-2-1

Low Smoke classification based on 3 metre cube test

Completed cables comply with the requirements of fire test BS4066-3 Category 3

Minimum Bending Radius

Single Cores: 15 x overall diameter
Three Cores: 12 x overall diameter

(Single Cores 12 x overall diameter and 3 cores 10 x overall diameter where bands are positioned adjacent to joint or terminations provided that the bending is carefully controlled by the use of a former)

Dimensions

Eland Part Number	No. of Cores x Nominal Cross Sectional Area # x mm ²	Nominal Diameter			Nominal Weight kg/Km
		Under Armour	Over Armour	Overall	
		mm			
A9M11KV01050L*	1 x 50	21.7	24.9	28.5	1200
A9M11KV01070L*	1 x 70	23.0	26.2	30.0	1500
A9M11KV01095L*	1 x 95	24.7	27.9	31.7	1600
A9M11KV01120L*	1 x 120	26.7	29.9	33.9	2100
A9M11KV01150L*	1 x 150	27.5	31.5	35.7	2500
A9M11KV01185L*	1 x 185	29.3	33.3	37.5	2900
A9M11KV01240L*	1 x 240	31.6	35.6	40.0	3600
A9M11KV01300L*	1 x 300	34.6	38.6	43.0	4300
A9M11KV01400L*	1 x 400	37.0	41.0	45.8	5200
A9M11KV01500L*	1 x 500	40.5	45.5	50.5	6500
A9M11KV01630L*	1 x 630	44.6	49.6	54.8	8000
A9M11KV01800L*	1 x 800	48.8	53.8	59.2	9850
A9M11KV011000L*	1 x 1000	53.5	58.5	64.3	12100
A9M11KV03025L*	3 x 25	39.0	44.0	48.8	4300
A9M11KV03035L*	3 x 35	41.6	46.6	51.6	4700
A9M11KV03050L*	3 x 50	44.4	49.4	54.6	5300
A9M11KV03070L*	3 x 70	48.1	53.1	58.5	6300
A9M11KV03095L*	3 x 95	52.0	57.0	62.6	7300
A9M11KV03120L*	3 x 120	55.6	60.6	66.6	8400
A9M11KV03150L*	3 x 150	58.6	63.6	69.8	9600
A9M11KV03185L*	3 x 185	62.7	67.7	74.1	11000
A9M11KV03240L*	3 x 240	68.1	74.4	81.2	14000
A9M11KV03300L*	3 x 300	73.5	79.8	87.0	16600

Conductors

Class 2 stranded conductors for Single Core and Multi-Core cables

1	2	3	4	5	6	7	8
Nominal Cross Sectional Area mm ²	Minimum Number of Wires in the Conductor						Maximum Resistance of Conductor at 20°C Annealed Copper Conductor Plain Wires ohms/Km
	Circular		Circular Compacted		Shaped		
	Cu	Al	Cu	Al	Cu	Al	
50.00	19	19	6	6	6	6	0.3870
70.00	19	19	12	12	12	12	0.2680
95.00	19	19	15	15	15	15	0.1930
120.00	37	37	18	15	18	15	0.1530
150.00	37	37	18	15	18	15	0.1240
185.00	37	37	30	30	30	30	0.0991
240.00	37	37	34	30	34	30	0.0754
300.00	61	61	34	30	34	30	0.0601
400.00	61	61	53	53	53	53	0.0470
500.00	61	61	53	53	53	53	0.0366
630.00	91	91	53	53	53	53	0.0283
800.00	91	91	53	53	-	-	0.0221
1000.00	91	91	53	53	-	-	0.0176

Electrical Characteristics

Copper Conductor Dimensions and Current Carrying Capacity (amperes)

No. of Cores x Nominal Cross Sectional Area	Continuous Current Rating in Ground Amps		Continuous Current Rating in Ducts Amps		Continuous Current Rating in Air Amps		
	# x mm ²	Trefoil	Flat	Trefoil	Flat	Trefoil	Flat
1 x 50		220	230	220	220	250	300
1 x 70		270	280	260	270	310	370
1 x 95		320	335	305	325	375	460
1 x 120		360	380	340	370	430	530
1 x 150		410	430	375	410	490	600
1 x 185		455	485	410	460	550	690
1 x 240		520	560	470	540	650	820
1 x 300		580	640	500	610	740	940
1 x 400		650	730	530	690	840	1100
1 x 500		710	830	570	780	930	1280
1 x 630		760	940	620	890	1040	1480
1 x 800		810	1060	660	990	1140	1690
1 x 1000		860	1170	690	1090	1230	1900
3 x 25		140	140	125	125	145	145
3 x 35		170	170	150	150	175	175
3 x 50		210	210	180	180	220	220
3 x 70		250	250	215	215	270	270
3 x 95		300	300	255	255	330	330
3 x 120		340	340	290	290	380	380
3 x 150		380	380	330	330	430	430
3 x 185		430	430	370	370	490	490
3 x 240		500	500	430	430	570	570
3 x 300		540	540	470	470	650	650

Correction Factors

Air Temperature	25°C	30°C	35°C	40°C	45°C	50°C	55°C
Correction Factor	1.00	0.96	0.92	0.88	0.83	0.78	0.73
Ground Temperature	10°C	15°C	20°C	25°C	30°C	35°C	40°C
Correction Factor	1.03	1.00	0.97	0.93	0.89	0.86	0.82
Ground Thermal Resistivity	0.9	1.0	1.2	1.5	2.0	2.5	3.0
Correction Factor	1.06	1.04	1.00	0.92	0.82	0.74	0.68
Depth of Laying_m	0.80	1.00	1.25	1.50	1.75	2.00	2.50
Correction Factor	1.00	0.97	0.95	0.94	0.93	0.91	0.90

The information contained within this datasheet is for guidance only. When selecting accessories such as cleats, glands, etc please note that actual cable dimensions may vary due to manufacturing tolerances.