

Cable Gland BW

Eland Product Group FCG

Application

2 part BW Brass cable glands are suitable for Steel Wired Armour cables. No loose parts enables easy installation. These glands are suitable for internal use.

Standards

BS6121 Part 1
 IP54 (Ingress Protection – dust protected, protected against splashing water)

Gland Material

Brass

Cable Type

SWA (Steel Wire Armour)

Armour Clamping

Two part armour lock



Dimensions

Gland Size	Metric Entry Thread mm	Minimum Thread Length mm	Bedding Diameter Max. mm	Outer Sheath Diameter Max. mm	Armour Wire Diameter mm	Across Corners Diameter Max. mm
20s	20	10	11.6	16.1	0.9/1.25	24.0
20	20	10	13.9	21.1	0.9/1.26	30.0
25	25	10	19.9	27.4	1.25/1.60	36.0
32	32	10	26.2	34.4	1.6/2.00	44.5
40	40	15	32.1	42.4	1.6/2.00	56.3
50s	50	15	38.1	50.1	2.0/2.50	63.4
50	50	15	44.0	55.7	2.0/2.50	72.1
63s	63	15	50.0	62.4	2.50	83.0
60	63	15	55.9	68.2	2.50	88.7
75s	75	15	61.9	76.8	2.50	99.8
75	75	15	67.9	82.9	2.5/3.15	105.3