

Cable Gland CX

Eland Product Group FCG

Application

CX brass cable glands are suitable for use with wire braid armoured cable. They provide electrical continuity of wire braid.

Standards

BS6121 Part 1

IP66 (Ingress Protection – dust tight, with a vacuum applied to the product, protected against powerful water jets.)

Gland Material

Brass

Cable Type

Wire Braid or Steel Tape Armour

Armour Clamping

Three part armour lock

Sealing

TPE (Thermoplastic Elastomer)



Dimensions

Gland Size	Metric Entry Thread mm	Minimum Thread Length mm	Bedding Diameter Max. mm	Outer Sheath Diameter Min. mm	Outer Sheath Diameter Max. mm	Braid/STA Thickness Max. mm	Across Corners Diameter Max. mm
20/16	20	15	8.6	6.0	13.4	0.85	24.4
20s	20	10	11.6	9.5	15.9	0.85	26.6
20	20	10	13.9	12.5	20.9	0.9	33.3
25	25	10	19.9	17.0	26.2	1.25	40.5
32	32	10	26.2	22.9	33.9	1.40	51.0
40	40	15	32.1	26.0	40.4	1.40	61.0
50s	50	15	38.1	35.0	46.7	1.40	66.5
50	50	15	44.0	38.0	53.1	1.40	77.7
63s	63	15	50.0	45.6	59.4	1.50	83.2
63	63	15	55.9	54.6	65.9	1.50	88.7
75s	75	15	61.9	57.6	72.1	1.50	101.6
75	75	15	67.9	60.4	78.5	1.50	111.1
90	90	15	79.3	69.2	90.4	1.60	128.6