

Cord End Terminals

Eland Product Group **FET**



Application

Cord End Terminals are designed to terminate the end of a cable, prior to fitting screw type terminal blocks or connectors. The crimped on cord end terminal then protects the exposed wire strands from damage from the screw, which results in a stronger connection.

Standards

DIN 46228 Part 4

Technical Data

Material

Tinned Copper

Dimensions

French Colour Range

Eland Part Number	Cable Size mm ²	Colour	Total Length mm	Pin Length mm	Pin Width mm	Pin Wall Thickness mm	Entry Width mm
FET0.25F	0.25	Violet	10.4	6.0	0.8	0.15	1.8
FET0.5F	0.50	White	14.0	8.0	1.0	0.15	2.6
FET0.75F	0.75	Blue	14.6	8.2	1.2	0.15	2.8
FET1.0F	1.00	Red	14.6	8.2	1.4	0.15	3.0
FET1.5F	1.50	Black	14.6	8.2	1.7	0.15	3.5
FET2.5F	2.50	Grey	15.2	8.2	2.2	0.15	4.0
FET4.0F	4.00	Orange	16.5	9.0	2.8	0.20	4.4
FET6.0F	6.00	Green	20.0	12.0	3.5	0.20	6.3
FET10.0F	10.00	Brown	21.5	12.0	4.5	0.20	7.6
FET16.0F	16.00	Ivory	22.2	12.0	5.8	0.20	8.8
FET25F	25.00	Black	29.0	16.0	7.3	0.20	11.2
FET35F	35.00	Red	30.0	16.2	8.3	0.20	12.5
FET50F	50.00	Blue	36.0	19.0	10.3	0.30	15.0

German Colour Range

Eland Part Number	Cable Size mm ²	Colour	Total Length mm	Pin Length mm	Pin Width mm	Pin Wall Thickness mm	Entry Width mm
FET0.25	0.25	Lt Blue	10.4	6.0	0.8	0.15	1.8
FET0.34	0.34	Turquoise	10.4	6.0	0.8	0.15	2.0
FET0.5	0.50	Orange	14.0	8.0	1.0	0.15	2.6
FET0.75	0.75	White	14.6	8.2	1.2	0.15	2.8
FET1.0	1.00	Yellow	14.6	8.2	1.4	0.15	3.0
FET1.5	1.50	Red	14.6	8.2	1.7	0.15	3.5
FET2.5	2.50	Blue	15.2	8.2	2.2	0.15	4.0
FET4.0	4.00	Grey	16.5	9.0	2.8	0.20	4.4
FET6.0	6.00	Black	20.0	12.0	3.5	0.20	6.3
FET10.0	10.00	Ivory	21.5	12.0	4.5	0.20	7.6
FET16.0	16.00	Green	22.2	12.0	5.8	0.20	8.8
FET25	25.00	Brown	29.0	16.0	7.3	0.20	11.2
FET35	35.00	Beige	30.0	16.2	8.3	0.20	12.5
FET50	50.00	Olive	36.0	19.0	10.3	0.30	15.0

The information contained within this datasheet is for guidance only – actual cable dimensions should be considered before making final selection as these may vary due to manufacturing tolerances.