

Generic Cable References

0361TQ	Welding cable, tinned copper conductor, EPR insulation, CSP sheathed. BS638
0361TQ (PC)	Welding cable, plain copper conductor, EPR insulation, CSP sheathed. BS638
0361TQ (AL)	Welding cable, aluminium conductor, EPR insulation, CSP sheathed. BS638
2093Y	3 Core, PVC heat resisting insulation/PVC heat resisting sheathed, Circular 300/300V BS6500 flexible cord.
218*Y	Circular, PVC insulation/PVC sheathed, 300/300V BS6500 flexible cord
2192Y	2 Core, PVC insulation/PVC sheathed Flat 300/300V BS6500 flexible cord
2213	3 Core, vulcanised rubber insulation/tough rubber sheathed/cotton braid, 300/300V BS6500 flexible cord.
2491X	Single core, PVC insulation 0.5mm ² - 1.00mm ² , 300/500V BS6500
2492X	Two, 2491X twisted, flexible cord.
309*Y	Circular, PVC heat resisting insulation/sheathed 300/500V BS6500 flexible cord
318*	Circular, vulcanised rubber insulation/tough rubber sheathed, 300/500V, flexible cord.
318*Y	Circular, PVC insulation/PVC sheathed, 300/500V, BS6500, flexible cord.
318*P	Circular, vulcanised rubber insulation/PCP sheathed, 300/500V BS6500 flexible cord.
318*TQ	Circular, EPR insulation/CSP sheathed, 300/500V, BS6500 flexible cord
3192Y	2 core, PVC insulation/PVC sheathed, flat 300/500V, BS6500 flexible cord.
380*Y	Circular, PVC insulation/PVC bedded/plain copper wire braid screened/PVC sheathed, 300/500V, BS6500, flexible cord.
380*P	Circular, vulcanised rubber insulation/tough rubber sheathed/tinned copper wire braid screened/PCP sheathed, 300/500V, BS6500, flexible cord.
380*T	Circular, EPR insulation/CSP bedded/tinned copper wire braid screened/CSP sheathed, 300/500V, BS6500, flexible cord.
398*	Heavy duty circular, vulcanised rubber insulation/PCP sheathed, 450/750V, BS6007, flexible cord.
618*Y	Circular, PVC insulation/PVC sheathed 1.00mm ² - 35mm ² , 300/500V, BS6004 50mm ² - 630mm ² generally in accordance with BS6346, wiring cable.
618*XY	Single core, XLPE insulation/PVC sheathed, 600/1000V, IEC502
6192P	2 core, vulcanised rubber insulation/PCP sheathed flat, 300/500V, BS6007 festoon wiring cable.
619*Y	Flat, PVC insulation/PVC sheathed, 300/500V, BS6004, wiring cable.
624*Y	Flat, PVC insulation laid up in parallel with a bare ECC within one interstice/PVC sheathed 300/500V, BS6004, wiring cable.
638*Y	Circular, PVC insulation/PVC sheathed, 300/500V, generally in accordance with BS6004 flexible cord.
638*TQ	Circular, EPR insulation/CSP sheathed, 450/750V, BS6007, flexible cable
6491X	Single core, PVC insulation 1.00mm ² - 630mm ² , 450/750V, BS6004
657*TQ	Circular, EPR insulation/CSP sheathed, 600/1000V, BS6883, shipwiring cable
657*TQ (S)	As 657*TQ but with shaped conductors instead of circular conductors.
658*TQ	Circular, EPR insulation/CSP bedding/galv mild steel wire braid armour/CSP sheathed 600/1000V, BS6883, shipwiring cable.
658*TQ (S)	As 658*TQ but with shaped conductors instead of circular conductors.
659*TQ	Circular, EPR insulation/CSP bedded/tinned phosphor bronze braid armour/PVC sheathed 600/1000V, BS6883, shipwiring cable.
659*TQ (S)	A 659*TQ but with shaped conductors instead of circular conductors.
6701X	Single core, PVC insulation 450/750V, flexible cord.
680*TQ	Circular, EPR insulation/CSP bedded/tinned copper wire braid screen/CSP sheathed, 450/750V, generally to BS6007, flexible cord.
694*X	Circular, PVC insulation/PVC bedded/single steel wire armoured/PVC sheathed, 600/1000V, BS6346, mains wire cable.
H01N2D	Single core, rubber insulation, 100/100V, BS638, welding flexible.
H07VVH6-F	Flat, PVC insulation/PVC sheathed, 450/750V, BS6977, festoon cable.

Generic Cable References

H07V-U	Single core, PVC insulation, 1.5mm ² - 2.5mm ² (solid), 450/750V, BS6004.
H05V-U	Single core, PVC insulation 1.0mm ² (solid), 300/500V, to BS6004.
H05RR-F	Circular, vulcanised rubber insulation/tough rubber sheathed, 300/500V, BS6500.
H03VV-F	Circular, PVC insulation/PVC sheathed, 300/300V, to BS6500.
H03VVH2-F	Flat 2 core, PVC insulation/PVC sheathed, 300/300V, to BS6500.
H05VV-F	Circular, PVC insulation/PVC sheathed, 300/500V, to BS6500.
H05VVH2-F	Flat 2 Core, PVC insulation/PVC sheathed, 300/500V, to BS6500.
H05V-K	Single core, PVC insulation 0.5mm ² - 1.0mm ² , 300/500V, to BS6500.
H07V-K	Single core, PVC insulation 1.5mm ² - 2.5mm ² , 450/750V, to BS6004.
H07RN-F	Circular, rubber insulated/rubber sheathed, 450/750V, to BS6007.
SIF	Silicone insulation single core flexible 300/500V.
SIHF	Silicone rubber insulation/Silicone rubber sheathed, 300/500V.
SIF-GL	Silicone insulation/lacquered glass-fibre braid protection, 300/500V
SIHF-GLS	Silicone insulation/Silicone bedded/galvanised steel wire braid protection 300/500V