

Individually Screened Multi-Pair Low Cap RS422 Cables (Belden Equivalent)

Eland Product Group **A3B**

Application

Audio, instrumentation and computer cables.

Standards

RS422

Conductor

Stranded tinned copper

Insulation

PE (Polyethylene)

Sheath

LSF (Low Smoke and Fume)

Screen

Individually screened pairs with aluminium foil screen

Sheath Colour

Grey

Voltage Rating

300V

Temperature Rating

80°C

Core Identification

9729LSF 2 Pairs: Black/Red, Black/White

9730LSF 3 Pairs: Black/Red, Black/White, Black/Green



Dimensions

Eland Part Number	Belden Alternative	No. of Pairs x Pair x AWG (No. of Strands) # x # x AWG(#)	Nominal Diameter of Strands mm	Nominal Overall Diameter mm	Nominal Weight kg/Km
A3B9729LSFGR	9729LSF	2 x 2 x AWG24(7)	0.2	7.4	55
A3B9730LSFGR	9730LSF	3 x 2 x AWG24(7)	0.2	8.1	68

Electrical Characteristics

Eland Part Number	Belden Alternative	Capacitance at 1kHz pF/m	Max Conductor Resistance ohms/Km
A3B9729LSFGR	9729LSF	50	85
A3B9730LSFGR	9730LSF	50	85