

Uninsulated Cord End Terminals

Eland Product Group **FCA**



Application

Uninsulated Cord End Terminals are designed to terminate the end of a cable, prior to fitting screw type terminal blocks or connectors. The crimped on uninsulated cord end terminal then protects the exposed wire strands from damage from the screw, which results in a stronger connection.

Technical Data

Material

Tinned Copper

Dimensions

Eland Part Number	Cable Size mm ²	Length mm	Width mm	Wall Thickness mm
FCUT 0.25-5	0.25	5	0.8	0.15
FCUT 0.5-6	0.50	6	1.0	0.15
FCUT 0.5-10	0.50	10	1.0	0.15
FCUT 0.75-6	0.75	6	1.2	0.15
FCUT 0.75-10	0.75	10	1.2	0.15
FCUT 1.0-6	1.00	6	1.4	0.15
FCUT 1.0-10	1.00	10	1.4	0.15
FCUT 1.5-7	1.50	7	1.7	0.15
FCUT 1.5-10	1.50	10	1.7	0.15
FCUT 2.5-7	2.50	7	2.2	0.15
FCUT 2.5-10	2.50	10	2.2	0.15
FCUT 4.0-9	4.00	9	2.8	0.20
FCUT 4.0-12	4.00	12	2.8	0.20
FCUT 6.0-12	6.00	12	3.5	0.20
FCUT 6.0-15	6.00	15	3.5	0.20
FCUT 10.0-12	10.00	12	4.5	0.20
FCUT 10.0-15	10.00	15	4.5	0.20
FCUT 10.0-18	10.00	18	4.5	0.20
FCUT 16.0-12	16.00	12	5.8	0.20
FCUT 16.0-15	16.00	15	5.8	0.20
FCUT 16.0-18	16.00	18	5.8	0.20
FCUT 25-15	25.00	15	7.3	0.20
FCUT 25-18	25.00	18	7.3	0.20
FCUT 25-25	25.00	25	7.3	0.20
FCUT 35-18	35.00	18	8.3	0.20
FCUT 35-25	35.00	25	8.3	0.20
FCUT 35-32	35.00	32	8.3	0.20
FCUT 50-18	50.00	18	10.3	0.30
FCUT 50-25	50.00	25	10.3	0.30
FCUT 50-32	50.00	32	10.3	0.30
FCUT 70-25	70.00	25	12.5	0.35
FCUT 95-30	95.00	30	14.5	0.35
FCUT 120-34	120.00	34	16.5	0.45
FCUT 150-38	150.00	38	18.5	0.50